

```
.hl_js { font-family: PT Mono; }
```

```
#!/bin/sh

apache_confptest() {
    [ -z "$CONFTEST_OUTFILE" ] || rm -f "$CONFTEST_OUTFILE"
    CONFTEST_OUTFILE=$(mktemp)
    if ! $APACHE2CTL configtest > "$CONFTEST_OUTFILE" 2>&1 ; then
        return 1
    else
        rm -f "$CONFTEST_OUTFILE"
        CONFTEST_OUTFILE=
        return 0
    fi
}

clear_error_msg() {
    [ -z "$CONFTEST_OUTFILE" ] || rm -f "$CONFTEST_OUTFILE"
    CONFTEST_OUTFILE=
    APACHE2_INIT_MESSAGE=
}
}
```

```
Mar 22 15:32:31 web-srv01 postfix/smtpd[13837]: connect from
localhost[127.0.0.1]
Mar 22 15:32:31 web-srv01 postfix/smtpd[13837]: 42BB512324B:
client=localhost[127.0.0.1]
Mar 22 15:32:31 web-srv01 postfix/cleanup[13839]: 42BB512324B: message-
id=<20150322193231.42BB512324B@mail.example.net>
Mar 22 15:32:31 web-srv01 postfix/qmgr[13834]: 42BB512324B:
from=<relay.test.2015@gmail.com>, size=427, nrcpt=1 (queue active)
Mar 22 15:32:31 web-srv01 postfix/smtpd[13837]: disconnect from
localhost[127.0.0.1]
Mar 22 15:32:31 web-srv01 postfix/smtp[13840]: setting up TLS connection to
smtp.googlemail.com[74.125.136.16]:25
Mar 22 15:32:31 web-srv01 postfix/smtp[13840]: Verified TLS connection
established to smtp.googlemail.com[74.125.136.16]:25: TLSv1.2 with cipher
ECDHE-RSA-AES128-GCM-SHA256 (128/128 bits)
Mar 22 15:32:32 web-srv01 postfix/smtp[13840]: 42BB512324B:
to=<relay.test.2015@mail.ru>, relay=smtp.googlemail.com[74.125.136.16]:25,
delay=1.6, delays=0.01/0/0.65/0.96, dsn=2.0.0, status=sent (250 2.0.0 OK
1427052699 nh17sm7809110wic.5 - gsmtpt)
Mar 22 15:32:32 web-srv01 postfix/qmgr[13834]: 42BB512324B: removed
```

```
<VirtualHost *:80>
    ServerAdmin webmaster@example.net
    ServerName gl-hooks.example.net
    ServerAlias example.net www.example.net

    DocumentRoot /vhosts/gl-hooks.example.net/
```

```
<Directory /vhosts/gl-hooks.example.net/>
  Options +ExecCGI -Indexes
  DirectoryIndex index.php
  AllowOverride All
  Order allow,deny
  Allow from all
</Directory>
</VirtualHost>
```

NGINX

```
server {
    listen      9898 default_server;
    server_name _;

    root /usr/share/nginx/html;
    error_log /var/log/nginx/header.log debug;

    location / {
        set $location L1;
        add_header X-DEBUG $show_debug_header always;
    }

    location =/test.html {
        set $location L2;
        add_header X-DEBUG $show_debug_header always;
    }
}
```

```
#!/bin/bash

##### BEGIN CONFIG
ACCEPTED_HOSTS="/root/.hag_accepted.conf"
BE_VERBOSE=false
##### END CONFIG

if [ "$UID" -ne 0 ]
then
    echo "Superuser rights is required"
    echo 'Printing the # sign'
    exit 2
fi

if test $# -eq 0
then
    elif test [ $1 == 'start' ]
```

```
else
fi

genApacheConf(){
  if [[ "$2" = "www" ]]
  then
    full_domain=$1
  else
    full_domain=$2.$1
  fi
  host_root="${APACHE_HOME_DIR}$1/$2/${title}"
  echo -e "# Host $1/$2 :"
}

```

```
Started by user Alex Domoradov
Building in workspace /var/lib/jenkins/jobs/test/workspace
> git rev-parse --is-inside-work-tree # timeout=10
Fetching changes from the remote Git repository
> git config remote.origin.url https://github.com/allinurl/goaccess.git #
timeout=10
Fetching upstream changes from https://github.com/allinurl/goaccess.git
> git --version # timeout=10
> git -c core.askpass=true fetch --tags --progress
https://github.com/allinurl/goaccess.git +refs/heads/*:refs/remotes/origin/*
> git rev-parse refs/remotes/origin/master^{commit} # timeout=10
> git rev-parse refs/remotes/origin/origin/master^{commit} # timeout=10
Checking out Revision b2ce7c70b1f3a51ef643dff0ca70ea097e54cb61
(refs/remotes/origin/master)
> git config core.sparsecheckout # timeout=10
> git checkout -f b2ce7c70b1f3a51ef643dff0ca70ea097e54cb61
> git rev-list b2ce7c70b1f3a51ef643dff0ca70ea097e54cb61 # timeout=10
[workspace] $ /bin/sh -xe /tmp/hudson1377791634779548631.sh
+ autoreconf -fiv
autoreconf: Entering directory `.'
autoreconf: configure.ac: not using Gettext
autoreconf: running: aclocal --force
autoreconf: configure.ac: tracing
autoreconf: configure.ac: not using Libtool
autoreconf: running: /usr/bin/autoconf --force
autoreconf: running: /usr/bin/autoheader --force
autoreconf: running: automake --add-missing --copy --force-missing
autoreconf: Leaving directory `.'
+ /var/lib/jenkins/jobs/test/workspace/configure --enable-geopip --enable-
utf8
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a thread-safe mkdir -p... /bin/mkdir -p
checking for gawk... no
checking for mawk... mawk

```

```
checking whether make sets $(MAKE)... yes
checking for gcc... gcc
checking whether the C compiler works... yes
checking for C compiler default output file name... a.out
checking for suffix of executables...
checking whether we are cross compiling... no
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking for style of include used by make... GNU
checking dependency style of gcc... gcc3

checking whether gcc and cc understand -c and -o together... yes
checking for pthread_create in -lpthread... yes
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking whether to build with rdynamic for GNU ld... yes
checking for GeoIP_new in -lGeoIP... yes
checking for mvaddwstr in -lncursesw... yes
checking for library containing stdscr... none required
checking for ncursesw/ncurses.h... yes
checking for ncurses.h... yes
checking for socket in -lsocket... no
checking for gethostbyname in -lnsl... yes
checking how to run the C preprocessor... gcc -E
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking arpa/inet.h usability... yes
checking arpa/inet.h presence... yes
checking for arpa/inet.h... yes
checking for inttypes.h... (cached) yes
checking limits.h usability... yes
checking limits.h presence... yes
checking for limits.h... yes
checking locale.h usability... yes
checking locale.h presence... yes
checking for locale.h... yes
checking netdb.h usability... yes
checking netdb.h presence... yes
checking for netdb.h... yes
```

```
checking netinet/in.h usability... yes
checking netinet/in.h presence... yes
checking for netinet/in.h... yes
checking stddef.h usability... yes
checking stddef.h presence... yes
checking for stddef.h... yes
checking for stdint.h... (cached) yes
checking for stdlib.h... (cached) yes
checking for string.h... (cached) yes
checking for strings.h... (cached) yes

checking sys/socket.h usability... yes
checking sys/socket.h presence... yes
checking for sys/socket.h... yes
checking for unistd.h... (cached) yes
checking for an ANSI C-conforming const... yes
checking for ptrdiff_t... yes
checking whether struct tm is in sys/time.h or time.h... time.h
checking for int64_t... yes
checking for int8_t... yes
checking for off_t... yes
checking for size_t... yes
checking for uint32_t... yes
checking for uint64_t... yes
checking for uint8_t... yes
checking for _LARGEFILE_SOURCE value needed for large files... no
checking for working memcmp... yes
checking whether time.h and sys/time.h may both be included... yes
checking for sys/time.h... yes
checking for unistd.h... (cached) yes
checking for alarm... yes
checking for working mktime... yes
checking whether lstat correctly handles trailing slash... yes
checking whether stat accepts an empty string... no
checking for strftime... yes
checking for working strtod... yes
checking for floor... no
checking for gethostbyaddr... yes
checking for gethostbyname... yes
checking for malloc... yes
checking for memmove... yes
checking for memset... yes

checking for realloc... yes
checking for realpath... yes
checking for regcomp... yes
checking for setlocale... yes
checking for strchr... yes
checking for strcspn... yes
checking for strdup... yes
checking for strerror... yes
```

```
checking for strncasecmp... yes
checking for strpbrk... yes
checking for strrchr... yes
checking for strspn... yes
checking for strstr... yes
checking for strtol... yes
checking for strtoull... yes
configure: creating ./config.status
config.status: creating Makefile
config.status: creating src/config.h
config.status: src/config.h is unchanged
config.status: executing depfiles commands
```

Your build configuration:

```
Prefix      : /usr/local
Package     : goaccess
Version     : 0.9.7
Storage method : On-memory Hash Database (Default)
GNU getline : no
Compiler flags : -pthread
Linker flags  : -lnsl -lncursesw -lGeoIP -lpthread
Bugs        : goaccess@prosoftcorp.com
```

+ make

```
debase=`echo src/browsers.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline  
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-  
initializers -pthread -MT src/browsers.o -MD -MP -MF $debase.Tpo -c -o  
src/browsers.o src/browsers.c &&\  
mv -f $debase.Tpo $debase.Po  
debase=`echo src/color.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline  
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-  
initializers -pthread -MT src/color.o -MD -MP -MF $debase.Tpo -c -o  
src/color.o src/color.c &&\  
mv -f $debase.Tpo $debase.Po  
debase=`echo src/commons.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline  
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-  
initializers -pthread -MT src/commons.o -MD -MP -MF $debase.Tpo -c -o  
src/commons.o src/commons.c &&\  
mv -f $debase.Tpo $debase.Po
```

```
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/csv.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/csv.o -MD -MP -MF $depbases.Tpo -c -o src/csv.o
src/csv.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/error.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/error.o -MD -MP -MF $depbases.Tpo -c -o
src/error.o src/error.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/gdashboard.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gdashboard.o -MD -MP -MF $depbases.Tpo -c -o
src/gdashboard.o src/gdashboard.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/gdns.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gdns.o -MD -MP -MF $depbases.Tpo -c -o
src/gdns.o src/gdns.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/gholder.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gholder.o -MD -MP -MF $depbases.Tpo -c -o
src/gholder.o src/gholder.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/gmenu.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
```

```
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gmenu.o -MD -MP -MF $depbasedir -c -o
src/gmenu.o src/gmenu.c &&\
mv -f $depbasedir $depbasedir.Po
depbasedir=`echo src/goaccess.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/goaccess.o -MD -MP -MF $depbasedir -c -o
src/goaccess.o src/goaccess.c &&\
mv -f $depbasedir $depbasedir.Po
depbasedir=`echo src/gstorage.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gstorage.o -MD -MP -MF $depbasedir -c -o
src/gstorage.o src/gstorage.c &&\
mv -f $depbasedir $depbasedir.Po
depbasedir=`echo src/json.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/json.o -MD -MP -MF $depbasedir -c -o
src/json.o src/json.c &&\
mv -f $depbasedir $depbasedir.Po
depbasedir=`echo src/opesys.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/opesys.o -MD -MP -MF $depbasedir -c -o
src/opesys.o src/opesys.c &&\
mv -f $depbasedir $depbasedir.Po
depbasedir=`echo src/options.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/options.o -MD -MP -MF $depbasedir -c -o
src/options.o src/options.c &&\
mv -f $depbasedir $depbasedir.Po
depbasedir=`echo src/output.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \
```



```
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/output.o -MD -MP -MF $depbases.Tpo -c -o
src/output.o src/output.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/parser.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/parser.o -MD -MP -MF $depbases.Tpo -c -o
src/parser.o src/parser.c &&
mv -f $depbases.Tpo $depbases.Po
src/parser.c: In function 'parse_specifier':
src/parser.c:1014:12: warning: ignoring return value of 'strtol', declared
with attribute warn_unused_result [-Wunused-result]
src/parser.c: In function 'read_log':
src/parser.c:2034:13: warning: ignoring return value of 'freopen', declared
with attribute warn_unused_result [-Wunused-result]

depbases=`echo src/sort.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/sort.o -MD -MP -MF $depbases.Tpo -c -o
src/sort.o src/sort.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/settings.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/settings.o -MD -MP -MF $depbases.Tpo -c -o
src/settings.o src/settings.c &&
mv -f $depbases.Tpo $depbases.Po
depbases=`echo src/ui.o | sed 's|[^/]*$|.deps/&;s|\\.o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline
-Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/ui.o -MD -MP -MF $depbases.Tpo -c -o src/ui.o
src/ui.c &&
mv -f $depbases.Tpo $depbases.Po
```

```
debase=`echo src/util.o | sed 's|[^/]*$|.deps/&;s|\.$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -\  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -\  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -\  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -\  
Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-\  
initializers -pthread -MT src/util.o -MD -MP -MF $debase.Tpo -c -o -\  
src/util.o src/util.c &&\  
mv -f $debase.Tpo $debase.Po  
debase=`echo src/xmalloc.o | sed 's|[^/]*$|.deps/&;s|\.$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -\  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -\  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -\  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -\  
Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-\  
initializers -pthread -MT src/xmalloc.o -MD -MP -MF $debase.Tpo -c -o -\  
src/xmalloc.o src/xmalloc.c &&\  
mv -f $debase.Tpo $debase.Po  
debase=`echo src/gkhash.o | sed 's|[^/]*$|.deps/&;s|\.$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -\  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -\  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -\  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -\  
Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-\  
initializers -pthread -MT src/gkhash.o -MD -MP -MF $debase.Tpo -c -o -\  
src/gkhash.o src/gkhash.c &&\  
mv -f $debase.Tpo $debase.Po  
  
debase=`echo src/geolocation.o | sed 's|[^/]*$|.deps/&;s|\.$||'`;\  
gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR=\"/usr/local/etc\" -\  
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -\  
Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -\  
Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -\  
Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-\  
initializers -pthread -MT src/geolocation.o -MD -MP -MF $debase.Tpo -c -o -\  
src/geolocation.o src/geolocation.c &&\  
mv -f $debase.Tpo $debase.Po  
gcc -O2 -DSYSCONFDIR=\"/usr/local/etc\" -Wno-long-long -Wall -W -Wnested-\  
externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-\  
declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -\  
Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -\  
Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -\  
rdynamic -o goaccess src/browsers.o src/color.o src/commons.o src/csv.o -\  
src/error.o src/gdashboard.o src/gdns.o src/gholder.o src/gmenu.o -\  
src/goaccess.o src/gstorage.o src/json.o src/opesys.o src/options.o -\  
src/output.o src/parser.o src/sort.o src/settings.o src/ui.o src/util.o -\  
src/xmalloc.o src/gkhash.o src/geolocation.o -lnsl -lcursesw -lGeoIP -\  
lpthread  
Finished: SUCCESS
```

From:
<http://sys-adm.org.ua/> - **wiki.sys-adm.org.ua**

Permanent link:
<http://sys-adm.org.ua/fonts2?rev=1455818089>

Last update: **2016/02/18 19:54**

