

```
<VirtualHost *:80> ServerAdmin webmaster@example.net ServerName gl-hooks.example.net
ServerAlias example.net www.example.net DocumentRoot /vhosts/gl-hooks.example.net/ <Directory
/vhosts/gl-hooks.example.net/> Options +ExecCGI -Indexes DirectoryIndex index.php AllowOverride
All Order allow,deny Allow from all </Directory> </VirtualHost>
```

NGINX

```
server { listen 9898 default_server; server_name _; root /usr/share/nginx/html; error_log
/var/log/nginx/header.log debug; location / { set $location L1; add_header X-DEBUG
$show_debug_header always; } location =/test.html { set $location L2; add_header X-DEBUG
$show_debug_header always; } }
```

```
#!/bin/bash ##### BEGIN CONFIG ACCEPTED_HOSTS="/root/.hag_accepted.conf"
BE_VERBOSE=false ##### END CONFIG if [ "$UID" -ne 0 ] then echo "Superuser rights is required"
echo 'Printing the # sign' exit 2 fi if test $# -eq 0 then elif test [ $1 == 'start' ] else fi
genApacheConf() { if [[ "$2" = "www" ]] then full_domain=$1 else full_domain=$2.$1 fi
host_root="${APACHE_HOME_DIR}$1/$2/${title}" echo -e "# Host $1/$2 :"
```

```
Started by user Alex Domoradov Building in workspace /var/lib/jenkins/jobs/test/workspace > git rev-
parse --is-inside-work-tree # timeout=10 Fetching changes from the remote Git repository > git
config remote.origin.url https://github.com/allinurl/goaccess.git # timeout=10 Fetching upstream
changes from https://github.com/allinurl/goaccess.git > git --version # timeout=10 > git -c
core.askpass=true fetch --tags --progress https://github.com/allinurl/goaccess.git
+refs/heads/*:refs/remotes/origin/* > git rev-parse refs/remotes/origin/master^{commit} #
timeout=10 > git rev-parse refs/remotes/origin/origin/master^{commit} # timeout=10 Checking out
Revision b2ce7c70b1f3a51ef643dff0ca70ea097e54cb61 (refs/remotes/origin/master) > git config
core.sparsecheckout # timeout=10 > git checkout -f b2ce7c70b1f3a51ef643dff0ca70ea097e54cb61
> git rev-list b2ce7c70b1f3a51ef643dff0ca70ea097e54cb61 # timeout=10 [workspace] $ /bin/sh -xe
/tmp/hudson1377791634779548631.sh + autoreconf -fiv autoreconf: Entering directory `.'
autoreconf: configure.ac: not using Gettext autoreconf: running: aclocal --force autoreconf:
configure.ac: tracing autoreconf: configure.ac: not using Libtool autoreconf: running: /usr/bin/autoreconf
--force autoreconf: running: /usr/bin/autoheader --force autoreconf: running: automake --add-missing -
-copy --force-missing autoreconf: Leaving directory `.' + /var/lib/jenkins/jobs/test/workspace/configure
--enable-geop --enable-utf8 checking for a BSD-compatible install... /usr/bin/install -c checking
whether build environment is sane... yes checking for a thread-safe mkdir -p... /bin/mkdir -p checking
for gawk... no checking for mawk... mawk checking whether make sets $(MAKE)... yes checking for
gcc... gcc checking whether the C compiler works... yes checking for C compiler default output file
name... a.out checking for suffix of executables... checking whether we are cross compiling... no
checking for suffix of object files... o checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes checking for gcc option to accept ISO C89... none needed
checking for style of include used by make... GNU checking dependency style of gcc... gcc3 checking
whether gcc and cc understand -c and -o together... yes checking for pthread_create in -lpthread...
yes checking build system type... x86_64-unknown-linux-gnu checking host system type... x86_64-
unknown-linux-gnu checking whether to build with rdynamic for GNU ld... yes checking for GeolP_new
in -lGeolP... yes checking for mvaddwstr in -lncursesw... yes checking for library containing stdscr...
none required checking for ncursesw/ncurses.h... yes checking for ncurses.h... yes checking for socket
in -lsocket... no checking for gethostbyname in -lnsl... yes checking how to run the C preprocessor...
gcc -E checking for grep that handles long lines and -e... /bin/grep checking for egrep... /bin/grep -E
checking for ANSI C header files... yes checking for sys/types.h... yes checking for sys/stat.h... yes
checking for stdlib.h... yes checking for string.h... yes checking for memory.h... yes checking for
```

strings.h... yes checking for inttypes.h... yes checking for stdint.h... yes checking for unistd.h... yes checking arpa/inet.h usability... yes checking arpa/inet.h presence... yes checking for arpa/inet.h... yes checking for inttypes.h... (cached) yes checking limits.h usability... yes checking limits.h presence... yes checking for limits.h... yes checking locale.h usability... yes checking locale.h presence... yes checking for locale.h... yes checking netdb.h usability... yes checking netdb.h presence... yes checking for netdb.h... yes checking netinet/in.h usability... yes checking netinet/in.h presence... yes checking for netinet/in.h... yes checking stddef.h usability... yes checking stddef.h presence... yes checking for stddef.h... yes checking for stdint.h... (cached) yes checking for stdlib.h... (cached) yes checking for string.h... (cached) yes checking for strings.h... (cached) yes checking sys/socket.h usability... yes checking sys/socket.h presence... yes checking for sys/socket.h... yes checking for unistd.h... (cached) yes checking for an ANSI C-conforming const... yes checking for ptrdiff_t... yes checking whether struct tm is in sys/time.h or time.h... time.h checking for int64_t... yes checking for int8_t... yes checking for off_t... yes checking for size_t... yes checking for uint32_t... yes checking for uint64_t... yes checking for uint8_t... yes checking for _LARGEFILE_SOURCE value needed for large files... no checking for working memcmp... yes checking whether time.h and sys/time.h may both be included... yes checking for sys/time.h... yes checking for unistd.h... (cached) yes checking for alarm... yes checking for working mktime... yes checking whether lstat correctly handles trailing slash... yes checking whether stat accepts an empty string... no checking for strptime... yes checking for working strtod... yes checking for floor... no checking for gethostbyaddr... yes checking for gethostbyname... yes checking for malloc... yes checking for memmove... yes checking for memset... yes checking for realloc... yes checking for realpath... yes checking for regcomp... yes checking for setlocale... yes checking for strchr... yes checking for strcspn... yes checking for strdup... yes checking for strerror... yes checking for strncasecmp... yes checking for strpbrk... yes checking for strrchr... yes checking for strspn... yes checking for strstr... yes checking for strtol... yes checking for strtoull... yes configure: creating ./config.status config.status: creating Makefile config.status: creating src/config.h config.status: src/config.h is unchanged config.status: executing depfiles commands Your build configuration: Prefix : /usr/local Package : goaccess Version : 0.9.7 Storage method : On-memory Hash Database (Default) GNU getline : no Compiler flags : -pthread Linker flags : -lnsl -lncursesw -lGeoIP -lpthread Bugs : goaccess@prosoftcorp.com + make depbase=`echo src/browsers.o | sed 's[[^/]*\$.deps/&;s|\.o\$||]'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/browsers.o -MD -MP -MF \$depbase.Tpo -c -o src/browsers.o src/browsers.c && \ mv -f \$depbase.Tpo \$depbase.Po depbase=`echo src/color.o | sed 's[[^/]*\$.deps/&;s|\.o\$||]'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/color.o -MD -MP -MF \$depbase.Tpo -c -o src/color.o src/color.c && \ mv -f \$depbase.Tpo \$depbase.Po depbase=`echo src/commons.o | sed 's[[^/]*\$.deps/&;s|\.o\$||]'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/commons.o -MD -MP -MF \$depbase.Tpo -c -o src/commons.o src/commons.c && \ mv -f \$depbase.Tpo \$depbase.Po depbase=`echo src/csv.o | sed 's[[^/]*\$.deps/&;s|\.o\$||]'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/csv.o -MD

```

-MP -MF $depbasedir -c -o src/csv.o src/csv.c && mv -f $depbasedir $depbasedir.Po depbase=`echo
src/error.o | sed 's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -
DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-
prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -
Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-
after-statement -Wno-missing-field-initializers -pthread -MT src/error.o -MD -MP -MF $depbasedir -c -o
src/error.o src/error.c && mv -f $depbasedir $depbasedir.Po depbase=`echo src/gdashboard.o | sed
's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -
Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls
-Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gdashboard.o -MD -MP -MF $depbasedir -c -o src/gdashboard.o
src/gdashboard.c && mv -f $depbasedir $depbasedir.Po depbase=`echo src/gdns.o | sed
's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -
Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls
-Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gdns.o -MD -MP -MF $depbasedir -c -o src/gdns.o src/gdns.c && mv -f
$depbasedir $depbasedir.Po depbase=`echo src/gholder.o | sed 's[^\/*$|.deps/&;s|.o$||]'`; gcc -
DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-
externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings
-Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-
align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/gholder.o
-MD -MP -MF $depbasedir -c -o src/gholder.o src/gholder.c && mv -f $depbasedir $depbasedir.Po
depbase=`echo src/gmenu.o | sed 's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -
DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-
prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -
Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-
after-statement -Wno-missing-field-initializers -pthread -MT src/gmenu.o -MD -MP -MF $depbasedir -c -o
src/gmenu.o src/gmenu.c && mv -f $depbasedir $depbasedir.Po depbase=`echo src/goaccess.o |
sed 's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc"
-Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -
Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls
-Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/goaccess.o -MD -MP -MF $depbasedir -c -o src/goaccess.o src/goaccess.c
&& mv -f $depbasedir $depbasedir.Po depbase=`echo src/gstorage.o | sed
's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -
Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -
Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls
-Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-
initializers -pthread -MT src/gstorage.o -MD -MP -MF $depbasedir -c -o src/gstorage.o src/gstorage.c
&& mv -f $depbasedir $depbasedir.Po depbase=`echo src/json.o | sed 's[^\/*$|.deps/&;s|.o$||]'`; gcc
-DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-
externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings
-Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-
align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/json.o -
MD -MP -MF $depbasedir -c -o src/json.o src/json.c && mv -f $depbasedir $depbasedir.Po
depbase=`echo src/opesys.o | sed 's[^\/*$|.deps/&;s|.o$||]'`; gcc -DHAVE_CONFIG_H -I. -I./src -O2 -
DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-
prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -
Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-

```

```
after-statement -Wno-missing-field-initializers -pthread -MT src/opesys.o -MD -MP -MF $depbasedir/opesys.o -c -o src/opesys.o src/opesys.c &&\ mv -f $depbasedir/opesys.o $depbasedir/opesys.o depbase=`echo src/options.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/options.o -MD -MP -MF $depbasedir/options.o -c -o src/options.o src/options.c &&\ mv -f $depbasedir/options.o $depbasedir/options.o depbase=`echo src/output.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/output.o -MD -MP -MF $depbasedir/output.o -c -o src/output.o src/output.c &&\ mv -f $depbasedir/output.o $depbasedir/output.o depbase=`echo src/parser.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/parser.o -MD -MP -MF $depbasedir/parser.o -c -o src/parser.o src/parser.c &&\ mv -f $depbasedir/parser.o $depbasedir/parser.o src/parser.c: In function 'parse_specifier': src/parser.c:1014:12: warning: ignoring return value of 'strtol', declared with attribute warn_unused_result [-Wunused-result] src/parser.c: In function 'read_log': src/parser.c:2034:13: warning: ignoring return value of 'freopen', declared with attribute warn_unused_result [-Wunused-result] depbase=`echo src/sort.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/sort.o -MD -MP -MF $depbasedir/sort.o -c -o src/sort.o src/sort.c &&\ mv -f $depbasedir/sort.o $depbasedir/sort.o depbase=`echo src/settings.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/settings.o -MD -MP -MF $depbasedir/settings.o -c -o src/settings.o src/settings.c &&\ mv -f $depbasedir/settings.o $depbasedir/settings.o depbase=`echo src/ui.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/ui.o -MD -MP -MF $depbasedir/ui.o -c -o src/ui.o src/ui.c &&\ mv -f $depbasedir/ui.o $depbasedir/ui.o depbase=`echo src/util.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/util.o -MD -MP -MF $depbasedir/util.o -c -o src/util.o src/util.c &&\ mv -f $depbasedir/util.o $depbasedir/util.o depbase=`echo src/xmalloc.o | sed 's|[^/]*|.deps/&;s|.o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-after-statement -Wno-missing-field-initializers -pthread -MT src/xmalloc.o -MD -MP -MF $depbasedir/xmalloc.o -c -o src/xmalloc.o src/xmalloc.c &&\ mv -f $depbasedir/xmalloc.o $depbasedir/xmalloc.o
```

```
depbases=`echo src/gkhash.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -
DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-
prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -
Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-
after-statement -Wno-missing-field-initializers -pthread -MT src/gkhash.o -MD -MP -MF $depbases.Tpo -
c -o src/gkhash.o src/gkhash.c && \ mv -f $depbases.Tpo $depbases.Po depbases=`echo
src/geolocation.o | sed 's|[^/]*$|.deps/&;s|\..o$||'`; \ gcc -DHAVE_CONFIG_H -I. -I./src -O2 -
DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-
prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -
Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-
after-statement -Wno-missing-field-initializers -pthread -MT src/geolocation.o -MD -MP -MF
$depbases.Tpo -c -o src/geolocation.o src/geolocation.c && \ mv -f $depbases.Tpo $depbases.Po gcc -O2 -
DSYSCONFDIR="/usr/local/etc" -Wno-long-long -Wall -W -Wnested-externs -Wformat=2 -Wmissing-
prototypes -Wstrict-prototypes -Wmissing-declarations -Wwrite-strings -Wshadow -Wpointer-arith -
Wsign-compare -Wredundant-decls -Wbad-function-cast -Winline -Wcast-align -Wextra -Wdeclaration-
after-statement -Wno-missing-field-initializers -pthread -rdynamic -o goaccess src/browsers.o
src/color.o src/commons.o src/csv.o src/error.o src/gdashboard.o src/gdns.o src/gholder.o src/gmenu.o
src/goaccess.o src/gstorage.o src/json.o src/opesys.o src/options.o src/output.o src/parser.o src/sort.o
src/settings.o src/ui.o src/util.o src/xmalloc.o src/gkhash.o src/geolocation.o -lnsl -lncursesw -lGeoIP -
lpthread Finished: SUCCESS
```

From:

<http://sys-adm.org.ua/> - **wiki.sys-adm.org.ua**

Permanent link:

<http://sys-adm.org.ua/hljs?rev=1455111161>

Last update: **2016/02/10 15:32**

